



Data Sheet

EPDM Rubber

A general purpose medium grade 65/70°sh EPDM/SBR, suitable for low pressure pipe seals, gaskets, weatherstrip, etc. Excellent water, ozone & UV resistant properties, vegetable oils, acids, aqueous chemicals, steam. Also has good mechanical properties and abrasion resistance. WRAS approved potable water grades are also available.

Unit 21 Priory Industrial Park
Airspeed Road
Christchurch
Dorset
BH23 4HD
Tel: 01425 278011
Fax: 01425 278012
www.deltarubber.co.uk
deltasales@deltarubber.co.uk

PROPERTY

TYPICAL VALUES

Base Polymer	Ethylene Propylene Diene Monomer
Colour	Black
Hardness	70° +/- 5° Shore A
Specific Gravity	1.4 gm/cm ³
Tensile Strength	5.0 Mpa
Elongation at break	300%
Tear Strength	12 kN/m
Compression Set (22hrs @ 70°C)	49%
Abrasion Resistance	490
Temperature Range	-35°C to +120°C

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable, but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied.



Cert No. GB08/75575

This product is REACH, RoHS, PAH & CE Compliant